

COASTLINE
Packaging, Inc.
30470 Energy Dr.
New Church, VA 23415

757-824-3831
www.prideantifreeze.com

ASTM/JIS-K
SPECIFICATIONS

D3306, D4985, D4340,

JIS-K2234-1994

APPLICATIONS

NOT FORMULATED FOR HD
DIESEL SERVICE

TOYOTA
LEXUS
SCION

Also Suitable For:

ACURA, DAEWOO

DAIHATSU

FORD WSSM97B55-A

GSA A-A870

HONDA, HYUNDAI, KIA

INFINITI, ISUZU

MAZDA, MITSUBISHI

NISSAN, SUBARU

SUZUKI

REMEMBER!
RECYCLE
USED
COOLANT

MADE IN USA



Pride ASIA SLL

**SUPER LONG LIFE HOAT
ANTIFREEZE/COOLANT Pre-diluted
FOR ASIAN
BRAND VEHICLES.**

PRODUCT BULLETIN

SEPTEMBER 2019

PRODUCT DESCRIPTION

PRIDE ASIA SLL is an extended life antifreeze/coolant for car and truck engines IN ASIAN MANUFACTURER BRANDS.

The heavy-duty *phosphated organic* formula is suitable for both gasoline and diesel vehicles. It can provide freeze protection to -34F and boil over protection to +265F (w/15psi).

It is fully compatible with all major brands of premium antifreeze/coolants brand cooling systems. It

does not contain recycled antifreeze, 2-EHA, silicate, amine, or nitrite.

PRIDE ASIA SLL can also be used in older Asian brand vehicles after a complete 'system' flush. The phosphate organic hybrid formula is also suitable for many US brand cars and light trucks.

PRIDE ASIA SLL protects against cooling system corrosion, and has anti-fouling, surface behavior, and lubricating properties.

CONTAINS

BITREX



**DO NOT MIX
WITH REGULAR
ANTIFREEZE**

COOLING SYSTEM RECOMMENDATIONS

A clean cooling system protects your vehicle/equipment investment. When changing coolant, always drain and flush your system thoroughly before refilling with recommended coolant. Maintain proper coolant levels. Always top-off with premix coolant. Change coolant regularly to remove contamination that may develop from engine gases or other fluids. Always follow manufacturers' service recommendation.

SPECIFICATIONS

	PREMIX
GLYCOL CONTENT	46 – 50%
INHIBITORS	> 2%
COLOUR	Pink
SPEC GRAVITY	1.07
pH (as supplied)	8.2 – 9.0
PHOSPHATE	Yes
FREEZE PT/BOIL PT	-34°F/+265°F (as is)