

COASTLINE
Packaging, Inc.
30470 Energy Dr.
New Church, VA 23415

757-824-3831
www.prideantifreeze.com

SPECIFICATIONS


ASTM D3306, D4985
AFNOR NFR15-601
BS 6580
CUNA NC 596-16
SAE J1034

**AUTOMOTIVE
APPLICATIONS**

AUDI, VOLKSWAGEN
ZVWZ37-105, G11 through G13
PORSCHE 774 C through 774G
BMW XL60069.0, 82141467704
81-229407454
BENTLEY-ROLLS ROYCE
BLATT –MAN 324 through 325
FIAT-CHRYSLER
FORD WSS-97MB444D,
ESE-978B4H-A
JAGUAR JLM 20972-1
LAND ROVER WSS97B44D
MERCEDES MB 324 through
325
MTL-MTU 5048
OPEL-GM B040-02, QL130100
93740141, 93740140
RENAULT
SAAB, SEAT, SKODA
VOLVO 9434699-8

MADE IN USA

www.prideantifreeze.com



Pride EUROTECH 84/34

**EXTENDED LIFE, ANTIFREEZE/ COOLANT
FOR EUROPEAN BRAND VEHICLES**

ENHANCED ORGANIC FORMULA

PRODUCT BULLETIN

APRIL 2021

PRODUCT DESCRIPTION

PRIDE EUROTECH is an extended life antifreeze/coolant formulation for cars and light trucks. It is available as either a concentrate (-84F) for installer dilution with quality water, or as a premix (-34F) for ready- to-use convenience. It can provide freeze protection to -84F and boil over protection to +276F (w/15psi). **DO NOT dilute the concentrate below 30%. NEVER dilute the premix.**

PRIDE EUROTECH is specifically formulated to meet requirements and specifications of *all EUROPEAN BRAND auto antifreeze/coolant.*

CONTAINS

BITREX

PRIDE EUROTECH is a poly-organic formula that is 2-EHA free. It is augmented with material specific inhibitors for alloy protection. Dispersants protect cooling system surfaces against scale to improve heat transfer, while surface-active agents improve distribution of the inhibitors on all wetted parts.

PRIDE UNIVERSAL does not contain any recycled antifreeze. This formula is free of amines, nitrite, and phosphate meeting requirements of European engines and cooling systems.

PRIDE EUROTECH is fully compatible with all European



specification Extended Life Coolants regardless of colour.

**RECYCLE
USED FLUID AND
CONTAINERS**

COOLING SYSTEM RECOMMENDATIONS

A clean cooling system protects your vehicle/equipment investment. When changing coolant, always drain and flush your system thoroughly before refilling with recommended coolant. Maintain proper coolant levels. Always top-off with premix coolant. Change coolant regularly to remove contamination that may develop from engine gases or other fluids. Always follow manufacturers' service recommendation.

SPECIFICATIONS

	CONCENTRATE	-34 PREMIX
GLYCOL CONTENT	95—96%	46 – 48%
INHIBITORS	> 4%	> 2%
COLOUR	Blue Violet	Blue Violet
SPEC GRAVITY	1.11-1.13	1.05-1.07
pH (as supplied)	8.0 – 9.0	8.0– 9.0 S
FREEZE PT/BOIL PT (as 50%)	-34F/+265F	-34F/+265F (as is)